



2012 CORPORATE LANE, SUITE 116 NAPERVILLE, IL 60563 TOLL FREE: 888-888-8045

Cable Plus Part #: 4070P

Description: 12 AWG, 2 conductor unshielded plenum rated cable constructed with stranded bare copper, polyvinylchloride insulation and an overall polyvinylchloride jacket for data communications/security applications manufactured in the USA and (UL) listed CL3P 75° C.

1. Conductor

- 1.1 AWG & Stranding: 12 AWG, 19 Strands
- 1.2 Material: Annealed Bare Copper

2. Insulation

- 2.1 Material: Plenum Rated Polyvinylchloride (SGPVC)
- 2.2 Wall Thickness: 0.009"

3. Color Code

- 3.1 Code: Black, Red

4. Assembly

- 4.1 Cable Lay Length: 3.25" LHL, Nominal
- 4.2 Cable Shield: N/A
- 4.3 Cable Drain Wire: N/A
- 4.4 Cable Binder: N/A
- 4.5 Ripcord: Yes

5. Jacket

- 5.1 Material: Plenum Rated Polyvinylchloride (SGPVC)
- 5.2 Wall Thickness: 0.015"
- 5.3 Diameter: 0.246"
- 5.4 Color: Natural
- 5.5 Weight: 56 lbs./Mft.

6. Markings

- 6.1 Type: Cable shall be permanently identified via surface inkjet print
- 6.2 Legend: TEMP CONTROL-ACCESS CONTROL-SOUND-SECURITY AI-DI-BI-AO-DO-BO
DEVICE OR ZONE ABCDEFG 1-2-3-4-5-6-7-8-9-10 E171202 12AWG 2C
(UL) CL3P 75°C "ROHS" FT-6
- 6.3 Ascending/descending footage markers

7. Standards

- 7.1 UL listed as Type CL3P c(UL)us 75° C.
- 7.2 All materials used in the manufacture of this cable are RoHS compliant

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION