



---

2012 CORPORATE LANE, SUITE 116 NAPERVILLE, IL 60563 TOLL FREE: 888-888-8045

**Cable Plus Part #: 7170**

**Description:** 14 AWG, 4 conductor unshielded riser rated cable constructed with solid bare copper, polyvinylchloride insulation and an overall polyvinylchloride jacket for data communications/ security applications manufactured in the USA and (UL) listed FPLR 75°C, FT-4.

**1. Conductor**

- 1.1 AWG & Stranding: 14 AWG, Solid
- 1.2 Material: Annealed Bare Copper

**2. Insulation**

- 2.1 Material: Polyvinylchloride (PVC)
- 2.2 Wall Thickness: 0.009"

**3. Color Code**

- 3.1 Code: Black, Red, Brown, Blue

**4. Assembly**

- 4.1 Cable Lay Length: 3.00" LHL, Nominal
- 4.2 Cable Binder: N/A
- 4.3 Cable Shield: N/A
- 4.4 Cable Drain Wire: N/A

**5. Jacket**

- 5.1 Material: Polyvinylchloride (PVC)
- 5.2 Wall Thickness: 0.015"
- 5.3 Diameter: 0.228"
- 5.4 Color: Red
- 5.5 Weight: 66lbs./Mft.
- 5.6 Ripcord: Yes

**6. Markings**

- 6.1 Type: Cable shall be permanently identified via surface inkjet print
- 6.2 Legend: "FIRE ALARM LIFE SAFETY" DEVICE OR ZONE INPUT OR OUTPUT ABCDEFG 1-2-3-4-5-6-7-8-9-10 E171203 14AWG 4C (UL) FPLR 75°C SUN RES FT-4 "ROHS" 6.3  
Ascending/descending footage markers prior to the legend

**7. Standards**

- 7.1 UL listed as Type FPLR 75°C, FT-4
- 7.2 All materials used in the manufacture of this cable are RoHS compliant

***ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION***