



CABLE PLUS INC.

Voice, Data, Sound & Security Products

2012 CORPORATE LANE, SUITE 116 NAPERVILLE, IL 60563 TOLL FREE: 888-888-8045

Part #: 7240PL

Description: 14 AWG, 2 conductor shielded plenum rated cable constructed with solid bare copper, polyvinylchloride insulation and an overall polyvinylchloride jacket for data communications / security applications manufactured in the USA and listed (UL) FPLP 75°C.

1. Conductor

- 1.1 AWG & Stranding: 14 AWG, Solid
- 1.2 Material: Annealed Bare Copper

2. Insulation

- 2.1 Material: Plenum Rated Polyvinylchloride (SGPVC)
- 2.2 Wall Thickness: 0.009"

3. Color Code

- 3.1 Code: Black, Red

4. Assembly

- 4.1 Cable Lay Length: 3.00" LHL, Nominal
- 4.2 Cable Shield: Aluminum Mylar
- 4.3 Cable Drain Wire: 24AWG 7 Strands Tinned Copper
- 4.4 Cable Binder: N/A

5. Jacket

- 5.1 Material: Plenum Rated Polyvinylchloride (SGPVC)
- 5.2 Wall Thickness: 0.015"
- 5.3 Diameter: 0.197"
- 5.4 Color: Red
- 5.5 Weight: 38 lbs./Mft.
- 5.6 Ripcord: Yes

6. Markings

- 6.1 Type: Cable shall be permanently identified via surface inkjet print
- 6.2 Legend: "FIRE ALARM LIFE SAFETY" DEVICE OR ZONE INPUT OR OUTPUT ABCDEFG
1-2-3-4-5-6-7-8-9-10 E171202 14AWG 2C (UL) CL3P OR (UL) FPLP 75°C
"ROHS" FT-6
- 6.3 Ascending/descending footage markers

7. Standards

- 7.1 UL listed as Type FPLP 75°C.
- 7.2 All materials used in the manufacture of this cable are RoHS compliant

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION