



2012 CORPORATE LANE, SUITE 116 NAPERVILLE, IL 60563 TOLL FREE: 888-888-8045

Part #: AV164C65-09

Description: 16 AWG, 4 conductor unshielded cable constructed with stranded bare copper OFC , polyvinylchloride insulation and an overall polyvinylchloride jacket for audio / Communications applications manufactured in the USA and (UL) listed CM or CL3 75° C.

1. Conductor

- 1.1 AWG & Stranding: 16 AWG, 65 Strands
- 1.2 Material: Annealed Bare Copper OFC

2. Insulation

- 2.1 Material: Polyvinylchloride (PVC)
- 2.2 Wall Thickness: 0.012"

3. Color Code

- 3.1 Code: Black, Red, White, Green

4. Assembly

- 4.1 Cable Lay Length: 3.25" LHL Nominal
- 4.2 Cable Shield: N/A
- 4.3 Cable Drain Wire: N/A
- 4.4 Cable Binder: N/A
- 4.5 Fillers: N/A

5. Jacket

- 5.1 Material: Polyvinylchloride (PVC)
- 5.2 Wall Thickness: 0.025"
- 5.3 Diameter: 0.250"
- 5.4 Color: White
- 5.5 Weight: 52.0 lbs. /Mft.

6. Markings

- 6.1 Type: Cable shall be permanently identified via surface inkjet print
- 6.2 Legend: AVALANCHE E171197 16AWG 4C 65STR OFC (UL) CL3 DIR BUR
OR CM C(UL)US SUN RES MADE IN USA L C R LS RS LR RR ROOM A B C D E F 1 2 3 4
5 6 7 8 9 JACK 1 2 3 4 5 6 7 8 9 WO# (WORK ORDER NUMBER) "ROHS"

7. Standards

- 7.1 UL listed as Type CL3 or CM 75° C
 - 7.2 All materials used in the manufacture of this cable are RoHS compliant
- ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**