



Comtran Cable LLC
 330A Turner Street
 South Attleboro, MA 02703-7714
 (P) 508-399-7004
 (F) 508-399-7360
 www.ComtranCorp.com

Design Specification Part Number: 5479 Category 5e Power Sum Plenum

Construction:

- * Conductors: 24 AWG Solid Bare Copper per ASTM B-3
- * Insulation: Fluoropolymer
- * Pair Assembly: Color Coded Conductors twisted to varying lays
- * Cable Assembly: 25 Pairs cabled around a filler to form round core
- * Jacket: White Fluoropolymer
Nominal OD = .455"
- * Ripcord: Ripcord provided under jacket
(Sequential Footage Marker Provided)

Compliance:

- * ETL Verified ANSI/TIA-568-C.2 (Cat 5e)
- * UL Subject 444 Communications Cables
- * UL Listed type CMP
- * NFPA 262 Plenum Flame Test
- * NEC Article 800
- * c(UL) Type CMP
- * ICEA S-80-576
- * CSA C22.2 No. 214
- * California State Fire Marshal
- * RoHS Compliant

Common Applications:

- | | | |
|--------------------------------------|------------------------|---------------------|
| * Gigabit Ethernet (1000Base-T) | * Video to the Desktop | * Multimedia |
| * High speed Voice/Data applications | * ISDN | * 55/155 Mbps ATM |
| * 100Base-TX | * 100Base-T | * 100Base VG-AnyLan |

Category 5e Electricals

(per ANSI/TIA 568-C.2)

	Char. Impedance	Return Loss	Attenuation	NEXT	PSNEXT	ELFEXT	PSELFEXT
Freq. (MHz)	(Ohms) (+/-15)	(dB) (Min)	(dB/100m) (Max)	(dB/100m) (Min)	(dB/100m) (Min)	(dB/100m) (Min)	(dB/100m) (Min)
1	100	20	2	65.3	62.3	63.8	60.8
4	100	23	4.1	56.3	53.3	51.7	48.7
8	100	24.5	5.8	51.8	48.8	45.7	42.7
10	100	25	6.5	50.3	47.3	43.8	40.8
16	100	25	8.2	47.3	44.3	39.7	36.7
20	100	25	9.3	45.8	42.8	37.7	34.7
25	100	24.3	10.4	44.3	41.3	35.8	32.8
31.25	100	23.6	11.7	42.9	39.9	33.9	30.9
62.5	100	21.5	17	38.4	35.4	27.8	24.8
100	100	20.1	22	35.3	32.3	23.8	20.8
Temp. Rating: 75c				Mutual Cap. = 14pf/ft		DC Res. = 9.38Ω/100m	
Nominal Velocity of Propagation (NVP) = 70%				Propagation Delay Skew: 45 ns/100m (max)			

(Information Subject to change without notice)

5480	Blue
5481	Gray

DRAWING	REV.	DATE	DRWN.	APP.	REMARKS	5479
35479	.05	5/27/11	2me	JB	Remove "-1"	
5479	.04	1/3/10	2me	JB	Revise Jacket	
5479	.03	12/9/10	2me	JB	Revised Format	
Page 1 of 1						