



2012 CORPORATE LANE, SUITE 116 NAPERVILLE, IL 60563
TOLL FREE: 888-888-8045

Part #: VNTC 18-4C NS
Unshielded Tray Cable
Specification

Description: 18 AWG 4 conductor 7 strand bare copper with polyvinylchloride and nylon insulation unshielded with an overall PVC jacket 600V tray cable, PLTC, NPLF & FPL, approved for use in SUN RES DIR BUR 90°C applications.

Conductor: AWG Size & Stranding: 18 AWG, 7 Strands Class B
 Material: Annealed Bare Copper
 Conductor Count: 4 Conductors

Insulation: Material: Polyvinylchloride & Nylon
 Wall Thickness: 0.015" PVC & 0.005" Nylon
 Color Code: Method 1, Table E-2

Assembly: Lay Length: 3.25" LHL
 Fillers: N/A
 Binder: N/A
 Shield: N/A
 Drain Wire: N/A

Jacket: Material: Polyvinylchloride
 Wall Thickness: 0.045"
 Diameter: 0.295"
 Color: Black
 Ripcord: Yes
 Cold Bend Rating: -40°C
 Weight: 55 lbs./Mft.

Markings: Type: Cable shall be permanently identified via surface inkjet print
 Legend: LAKE CABLE E207231 18AWG 4C (UL) NPLF 90°C 150V PVC/N OR PLTC OR FPL OR TC-ER 600V 90°C DRY/
 WET SUN RES DIR BUR PVC JACKET FT4 "ROHS II" MADE IN USA
 Footage Markers: Yes

Standards

- Refer to NEC (NFPA 70) article 336 for installation guidelines
- Cable is suitable for use in Class I Division II hazardous locations
- UL listed as Type TC-ER per UL Standard 1277 for tray cables and Quad Rated TC, PLTC, NPLF & FPL
- UL approved for Direct Burial and Sunlight Resistant applications
- Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
- Meets ICEA S-73-532, where applicable
- All materials used in the manufacture of this cable are RoHS II & REACH compliant
- Made in the USA

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION