



| ATRAS CAT 6A PATCH CORD | |
|-------------------------------|--|
| MATERIAL SPECIFICATIONS | |
| Construction | U/FTP, 4 Twisted Pair with Boot |
| Jacket Material | Polyvinyl Chloride (PVC) |
| Housing Material | Polycarbonate, UL 94V-0 |
| Conductor | 26 AWG Stranded Copper |
| Insulation | Polyethylene (PE) |
| Shielded | Aluminum Foil Shielded for each pair |
| Shield Material | Bronze with Nickel Plate |
| Contact Material | Phosphor Bronze with 50-60 micro-inch Nickel Plate |
| Contact Finish | Min 50 micro-inch Gold Plate on surface contact area |
| Plug | RJ45 |
| ETL Verified | To TIA-568-C.2 |
| PART NUMBERS | |
| ATS-PC8L03F-L6AB (3 FT-Blue) | ATS-PC8W03F-L6AB (3 FT-White) |
| ATS-PC8L05F-L6AB (5 FT-Blue) | ATS-PC8W05F-L6AB (5 FT-White) |
| ATS-PC8L07F-L6AB (7 FT-Blue) | ATS-PC8W07F-L6AB (7 FT-White) |
| ATS-PC8L10F-L6AB (10 FT-Blue) | ATS-PC8W10F-L6AB (10 FT-White) |
| ATS-PC8L15F-L6AB (15 FT-Blue) | ATS-PC8W15F-L6AB (15 FT-White) |



www.atrasusa.com 1-704-966-0324

CAT 6A PATCH CORD