



FEATURES	
Premium Quality	
Category 5E certified to meet all Cat 5E specifications	
Engineered for high speed transmissions for optical performance	
Color coded TIA/EIA 568A (international) & 568B (AT&T standard) wiring	
Industry standard 110 or Krone IDC connectors	
Rear Cable Management Bracket/Strain Relief Bar	
Includes tie wraps and mounting screws	
Panels include port numbering and write-on areas	
25 Year Warranty available	
MATERIAL STANDARDS	
Metal Frame	
IDC Plastic	PC, UL 94V-0
IDC Contacts	Phosphor bronze w/200u" Tin over 100u" Nickel undercoat
Spring Wire	Phosphor bronze w/ 50u" Gold over 100u" Nickel undercoat
Temperature	-40°C to 68°C
Humidity	10% to 90% RH
Modular Jack	750 mating cycles
IDC Block	200 termination cycles
ELECTRICAL STANDARDS	
Current Rating	1.5A
Voltage	150V
Insulation Resistance	500M Ohm
Contact Resistance	20m Ohm
DC Resistance	0.1 Ohm

MODEL ATS-C5E-24P		
www.atrasusa.com 1-704-966-0324	TITLE 24 PORT CAT 5E HORIZONTAL PATCH PANEL	